

SML/SEC/2019
23rd April, 2019

Dy. General Manager- Corporate Relationship Department BSE Limited P J Towers, Dalal Street, Fort Mumbai 400 001 Scrip Code: 505192	The Secretary National Stock Exchange of India Ltd. Exchange Plaza, 5th Floor Plot No. C/1, G Block Bandra – Kurla Complex Scrip Code: SMLISUZU
---	---

Dear Sir,

Intimation of Product Launch

Pursuant to Regulation 30 of SEBI (Listing Obligations and Disclosure Requirements) Regulations, 2015, intimation of product launch is enclosed as **Annexure I**.

This is for your information and record please.

Thanking you,

Yours faithfully,

For SML ISUZU LIMITED



(PARVESH MADAN)

Company Secretary & Compliance Officer

pmadan@smlisuzu.com

ACS-31266

SML ISUZU Limited

Corporate Office : 204-205, Sector 34-A, Chandigarh -160135

T +91 172 2647700-10 **F** +91 172 2615111

Regd. Office & Works:

Village : Asron, Distt. Shahid Bhagat Singh Nagar (Nawanshahar) Punjab -144533

T +91 1881 270255 **F** +91 1881 270223 **W** www.smlisuzu.com **CIN** L50101PB1983PLC005516

Trucks & Buses

Annexure I

Information required under SEBI (LODR) Regulations, 2015 is as under:

S No	Particulars	Product 1	Product 2
1	Name of the Product	Sartaj 5252 XM (CNG)	Ambulance (Compliant to AIS 125; Available in Type B, C & D)
2	Date of Launch	23 rd April, 2019	23 rd April, 2019
3	Category of the Product	Commercial Vehicle- Truck category	Ambulance
4	Whether caters to domestic/international market	Domestic market	Domestic market
5	Name of the countries in which the product is launched (in case of international)	Not Applicable	Not Applicable
6	Features of the Product	As per the attached Brochure	As per the attached Brochure

For SML ISUZU LIMITED



(PARVESH MADAN)
Company Secretary &
Compliance Officer
ACS-31266



SML
ISUZU

ECO-FRIENDLY & PROFITABLE



SARTAJ 5252 XM (CNG)

GVW : 4995 KG



**Class Leading
Turning Circle
Radius 5.1 m**



**High Rated
Payload: 2.3
Ton with 10' HD**



**Large
Loading Area :
5.67 sq. m**

TECHNICAL SPECIFICATIONS

Model	Sartaj 5252 XM (CNG)
ENGINE	
Make & Model	SML ISUZU, SLT NG
Type & Compliance	Dedicated CNG, BS-IV
No. of Cylinders, Displacement	4 in-line, 3455 cc
Performance	
Power	66.5 kW 2,800 ± 200 rpm
Torque	249 Nm @ 2,000 ± 50 rpm
Transmission	
Gearbox Model & Type	Synchromesh Manual 5 Forward + 1 Reverse
Clutch Diameter & Type	260 mm, Single Plate Diaphragm
Brakes & Type	
Service Brake	Vacuum Assisted Hydraulic Brakes
Tyre's Size & Nos.	7.00" x 16" - 14 PR (4+1)
Steering	
Type	Recirculating Ball Type
Power Steering	Optional
Suspension	
Type & Springs	Semi Elliptical with Multi Leaf Springs
Shock Absorber	Double Acting Hydraulic Dampers
Electricals	
System Voltage	12V
Battery Rating	70 Ah
Fuel Tank	
Material	Chrome Moly Steel (DS 202)
Capacity	140 l (2 Cyl. of 70 l)
Weight & Dimensions	
Gross Vehicle Weight (kg)	4,995
Wheel Base (mm)	2515
Cargo Area (L x W mm)	3050 x 1860 / 2745 x 1860
Cargo Length	10 ft. (Available in LSD, Semi-HD & HD)
Cabin Chassis	Available

Disclaimer : The specification may change without any prior notice, as per the cp.[amu]'s policy of continues improvement of its products/services. The pictures used are for indicative illustration purpose only, actual product may vary. All cargo dimensions are for quick reference purpose only. * Terms & Conditions Applied

SALIENT FEATURES



High On Fuel Efficiency



Low on Maintenance, Dependable Aggregates



Highly Safe



Environment Friendly Fuel



Aesthetically Designed Spacious Cabin



Features for Driver Convenience like mobile charging port

ALWAYS USE GENUINE SML ISUZU SPARES

WARRANTY *

- Engine & Transmission : 3 Years Unlimited km Run
- Vehicle : 1 Year Unlimited km Run.

AUTHORISED DEALER



S.C.O. 204-205, Sector 34-A, Chandigarh - 160022
Ph.: +91 172-2647700-10
website : www.smlisuzu.com E- mail : salesadm@smlisuzu.com

*T&C Apply

SPECIFICATIONS



Parameter	B Type PTV (Patient Transport Vehicle)	C Type BLS (Basic Life Support)	D Type ALS (Advance Life Support)
Wheel Base	2815mm	2815mm	2815mm
Emission Norm	BS - IV	BS - IV	BS - IV
Engine Capacity	3455cc	3455cc	3455cc
Engine Power	75 kW @ 2800 rpm	75 kW @ 2800 rpm	75 kW @ 2800 rpm
Power Steering	✓	✓	✓
No. of Tyres	4+1	4+1	4+1
Air Conditioning	Optional	Optional	✓
Overall Length mm	5579	5579	5579
Overall Width mm	2000	2000	2000
Automatic Roll-In stretchers Compliant to Type-B	Yes, Qty – 1 or 2 Compliant to Type-C	Yes, Qty – 1 or 2 Compliant to Type-D	Yes, Qty – 1 or 2
Interiors (Panel)	Soft Roof, Sheet Panel	FRP/Non-Permeable Material	FRP/Non-Permeable Material
Bar Light & Public Address System	✗	✓	✓
Revolving Light on top	✓, Blue Beacon Light	✗, Part of Bar Light	✗, Part of Bar Light
Side Blinkers & Flood Lights	✗	✓	✓
Dual Battery	✗	✓	✓
Provision/Space for Medical Equipment	✓	✓	✓
Extra Fitment (Not in Part-1 of AIS-125)			
Oxygen Delivery System Cylinder will be provided	✓, Clamp for mounting Cylinders	✓, with Compartment for 02 Cylinders	✓, with Compartment for 02
IV Bottle Hooks/Space	✓	✓	✓
Scoop Stretcher	✗	✗	✓
Spine Board	✗	✗	✓

• External Graphics as per ambulance code. • Medical Equipment/Medicines are NOT Included in the SML Supply Scope. Provision/Space will be provided
• Oxygen Cylinders are not Included. • Auto Changer Oxygen Supply System with Digital Display is available at Extra cost (for D type)



SML ISUZU LTD.
S.C.O. 204 -205, Sector 34-A, Chandigarh - 160022
Ph.: +91 172-2647700-10 Fax : +91 172-2615111
website : www.smlisuzu.com E- mail : sml.spv@smlisuzu.com

AUTHORISED DEALER



HOSPITAL



AIS-125
AMBULANCE
EQUIPPED TO CARE



• Fully Compliant to National Ambulance Code AIS-125 (Part-1) • Double Patient Capacity • External Power support for stationary use.