

API Documentation for Online Trade Inquiry Service

Version 1.5

March 2023



National Stock Exchange of India Ltd
Exchange Plaza, Plot No. C/1, G Block,
Bandra-Kurla Complex, Bandra (E)
Mumbai - 400 051.

Notice

© Copyright National Stock Exchange of India Ltd (NSEIL). All rights reserved.
Unpublished rights reserved under applicable copyright and trades secret laws.

The contents, ideas and concepts presented herein are proprietary and confidential.
Duplication and disclosure to others in whole, or in part is prohibited.

Table of Contents

1	Background	3
2	Data Flow Diagram.....	4
3	Technology Specification	5
4	API Registration	5
5	Log-In Workflow	6
6	Request/Response Structure (JSON)	8
7	Transcodes	17
8	Response Codes	19
9	Contingency	23
10	Usage Guidelines	23

Version	Date	Description
1.1	4 th June 2019	Added Usage Guidelines
1.2	29 th Nov 2019	Updated Interoperability Changes
1.3	19 th Oct 2020	Added filter for Clearing Member to view trades/actions as a Trading Member
1.4	09 th May 2022	Modification in Usage Guidelines
1.5	15 th March 2023	Added note for nonce header validation

1 Background

Currently trading system transfers online trades data to NSEIL Online Trade Inquiry System (NOTIS) server.

NOTIS client application residing at the members end sends periodical request to pull the data from the server. Maximum 'N' number of records (parameterized at server) are sent to the client application for each request. Currently trade data available on the NOTIS server is accessible only to the NOTIS client application.

It is proposed to expose API's to our esteemed empanelled members for trade & actions (any modifications performed on trade) inquiry for CD segment.

This document covers the technical specifications for various operations involved at both NSEIL as well as Members end.

- Following operations aspects are covered in this document:

Sr. No.	Operation	Endpoints	Purpose
1	Login [Handshake]	/token	To authenticate the client
2	Trade Inquiry	/notis-cd/trades-inquiry	To disseminate trades information data/Client Modifications
3	Trade Actions Inquiry	/notis-cd/actions-inquiry	Approval/Rejection/Approve All Confirmation/SI Download/CP Modifications

- Technical Specifications
- Log-in Work flow
- Message Structures


2 Data Flow Diagram

→ API Registration

- For API registration, user need to request the NSE team to add entry for them in database.
- The entry for user will be added from backend manually and no frontend will be provided for this purpose.
- Once entry is added the user will be provided with username & password to access the token API in order to get token.
- Once token is obtained user can access the Trade Inquiry API using below mentioned diagram.

→ API Call Work Flow

Member -> NSEIL



3 Technology Specification

- Communication Protocol: HTTPS over Leased line/Internet.
- Request/Response Exchange Format: JSON (JavaScript Object Notation).
- Data Format: CSV (Comma Separated Values).
- Security Framework: Security Framework should support OAuth 2.0 specifications.

4 API Registration

- Members need to register by contacting MSD (Member Service Department) for creating the user account details in the database.
- Member will need to provide information as described below:
- Service → Trade Inquiry Service
- Email Id → Email Address where the API credentials would be sent
- IP Address → IP Address from which the member will communicate with NSEIL API Service
- Once this information is provided, admin at NSEIL will verify & generate Consumer Key & Consumer Secret. These values will be emailed to MEMBER using registered email Id.
- Once MEMBER receives Consumer Key & Consumer Secret, they can start using API.

5 Log-In Workflow

- Login Handshake (MEMBER → NSEIL)
- Requesting a “Token”

NOTE: When sending the token request, member should request the token from one platform and share the generated token across multiple platforms to avoid the 500 error code that occurs when more than one token has been generated for a consumer key/secret.

A consumer application needs to send a HTTPS POST request to

UAT: <https://www.devconnect2nse.com/token>

Production/LIVE: <https://www.connect2nse.com/token>

➔ Sample Request

POST /token HTTP/1.1

Host: www.devconnect2nse.com

Content-Type: application/x-www-form-urlencoded

Authorization: Basic aGRmYzpoZGZjc2VjcmV0

nonce: MjAwMTIwMTcxNjEyMjE1OTE6ODk0MjY3

grant_type=client_credentials

➔ Request Structure

API AUTHENTICATION REQUEST STRUCTURE (GET TOKEN)				
Sr. No.	Parameter Name	Data Type	Description	Sample Value
1	Authorization	String	Will be of format: Basic <member_credentials> Where, member_credentials is a base64 encoding of the following data: cons_key:cons_secret	Basic aGRmYzpoZGZjc2VjcmV0
2	nonce	String	An N-once value, that uniquely identifies each request sent to server. Has to be a base64 encoding of the following data: ddMMyyyyHHmmssSSS:<6-digit random number>	MjAwMTIwMTcxNjEyMjE1OTE6 Note: A new nonce value will have to be sent for each subsequent request otherwise the member will face 401 error.

```
HTTP/1.1 200 OK
Content-Type: application/json
Pragma: no-cache{
  "access_token": "ee1073de-45d0-4040-b9c2-eddfa80280c0",
  "token_type": "bearer",
  "expires_in": "3600",
  "scope": "api_scope"
}
```

API AUTHENTICATION RESPONSE STRUCTURE (GET TOKEN)				
Sr. No.	Parameter Name	Data Type	Description	Sample Value
1	access_token	String	The access token issued by the authorization server.	eyJhbGciOiJIUzI1NiIsInR5cCI
2	token_type	String	The type of the token issued	bearer
3	expires_in	int	The lifetime in seconds of the access token. For example, the value "3600" denotes that the access token will expire in one hour from the time the response was generated.	32499
4	scope	String	If identical to the scope requested by the client otherwise, REQUIRED.	api scope

- The Access token is to be reused to access the NSE API Data till it expires.
- An access token expires after 'X' minutes of inactivity.

6 Request/Response Structure (JSON)

6.1 Trade Inquiry (ALL/TMTRADES Trades)

UAT: <https://www.devconnect2nse.com/notis-cd/trades-inquiry>

Production/LIVE: <https://www.connect2nse.com/notis-cd/trades-inquiry>

➔ Sample request call (ALL Trades)

```
POST /notis-cd/trades-inquiry HTTP/1.1
Host: www.devconnect2nse.com
Authorization: Bearer 3f64e567-04f9-43b8-9d24-e99856b24151
nonce: MjAwMTIwMTcxNjEyMjE1OTE6ODk0MjY3

{
  "version": "1.0",
  "data": {
    "msgId": "00240201310140000001",
    "dataFormat": "CSV:CSV",
    "tradesInquiry": "0,ALL,,"
  }
}
```

➔ Sample request call (TMTRADES Trades)

NOTE: This filter is only applicable to Clearing Members that want to view only the trades that they have performed as a Trading Member.

```
POST /api/notis-cd/trades-inquiry HTTP/1.1
Host: www.connect2nse.com
Authorization: Bearer 3f64e567-04f9-43b8-9d24-e99856b24151
nonce: MjAwMTIwMTcxNjEyMjE1OTE6ODk0MjY3

{
  "version": "1.0",
  "data": {
    "msgId": "00240201310140000001",
    "dataFormat": "CSV:CSV",
    "tradesInquiry": "0,TMTRADES,,"
  }
}
```

Request Data Payload (JSON)				
Sr. No.	Parameter Name	Data Type	Description	Sample Value
1	version	String	API version	1.0
2	data.msgId	String	Unique request number for the each request <CODE><YYYYMMDD><nnnnnnnn> • MEMBERCODE – Member code (Length : 5) • YYYYMMDD – Date format • nnnnnnn – Sequence no. starting from one i.e. For first request of the day, it should be (0000001).	00240201310140000001
2	data.dataformat	String	Request data format : Response data format	CSV:CSV
3	data.tradesInquiry	CSV	Data Structure specified below	0,ALL,,

Trade Inquiry Request Packet Structure				
Field Name	Description	Data Type	Size (in bytes)	Sample
seqNo	Trade Sequence number till where server had already sent data information In the previous request. For first download request of the day, it should be 0.	long	8	0
srchFilter	Search Filter	String	50	<ul style="list-style-type: none"> ALL – All Trades TMTRADES – Clearing Member to view trades as a Trading Member (Only applicable to Clearing Members)
fill1	Filler	String	10	
fill2	Filler	String	10	

➔ Sample Response



→ Control Record
 → Record Separator
 → Data Record(s)

```
{
  "status": "success",
  "messages": {
    "code": "01010000"
  },
  "data": {
    "msgId": "00240201310140000001",
    "tradesInquiry":
      1,20160101,,117833,1,116426,1,116426,82441285773058,6109,21,715350000,1,10000000007
      53545,4,1497,1,B83L005,AXISX0000001,,2,6001,1257953964,1,,400028023057130,P,09018,USD
      INR, ,FUTCUR,1259280000,-1,
      ,117833,1,49404,82441309921114,6109,18,715325000,2,10000000000302909,4,1497,1,B7
      4A111,09018,,106,5445,1257941616,1,,700071021007130,P,09018,USDINR,
      ,FUTCUR,1259280000,-1, ,,,,,,
  }
}
```

➔ Response Structure

Response Data Payload (JSON)				
Sr. No.	Parameter Name	Data Type	Description	Sample Value
1	status	String	Response status	success/error
2	messages.code	String	Refer Section “Message based response code”.	01010000.
3	data.msgId	String	Unique request number sent in request.	00240201310140000001
4	data.tradesInquiry	CSV	Data Structure specified below	Refer Sample Response.

Trade Inquiry Response Packet Structure				
Field Name	Description	Data Type	Size (in bytes)	Remarks
Control Record				
sysinfoResData	System Info Response Structure	System Info Response Structure	Size of (System Info Response Structure)	Structure details give below

trdResData	Trades Response Data Structure	Response Data Structure	Size of Response Data Structure	Structure details give below
------------	--------------------------------	-------------------------	---------------------------------	------------------------------

➔ System Info Response Structure

System Info Response Structure				
Field Name	Description	Data Type	Size (in bytes)	Sample
mktSts	Market Status Refer Section "Transcodes".	Short	2	2
currTrdDate	Current Trade Date (YYYYMMDD)	long	8	20160101
sfill1	Filler	String	10	
sfill2	Filler	String	10	

➔ Trade Response Data Structure

Trades Response Data Structure				
Field Name	Description	Data Type	Size (in bytes)	Sample/Remarks
maxSeqNo	Max sequence number sent in response	long	8	117833
noOfRec	Count of trades sent in the response	Int	4	2
Data Records				
tradesOutput	Array Of Trade Structure	Array Of Trade Structure	Size of (Array Of Trade Structure)	Structure details given below

Array Of Trade Structure					
Sr No.	Field Name	Description	Data Type	Size (in bytes)	Sample
1	seqNo	Unique Sequence Number	long	8	116426
2	mkt	Market Type. Refer Section "Transcodes"	String	1	1
3	trdNo	Trade Number	long	8	116426
4	trdTm	Trade Time in Jiffy Format	long	8	82441285773058
5	tkn	Token	int	4	6109

6	trdQty	Trade Quantity	int	4	21
7	trdPrc	Trade Price in paise	int	4	715350000
8	bsFlg	Buy Sell Flag. Refer Section "Transcodes"	String	1	1
9	ordNo	Order Number	double	8	1000000000753545
10	brnCd	Branch Code	int	4	4
11	usrId	User Id	int	4	1497
12	proCli	Client Type. Refer Section "Transcodes"	short	2	1
13	cliActNo	Client account number	String	20	B83L005
14	cpCd	Custodial participant Id	String	12	AXISX0000001
15	remarks	Remarks	String	25	
16	actTyp	Activity Type. Refer Section "Transcodes"	short	2	2
17	TCd	Transaction Code. Refer Section "Transcodes"	short	2	6001
18	ordTm	Order Time in milliseconds from 1980	long	8	1257953964
19	booktype	Book Type. Refer Section "Transcodes"	short	2	1
20	oppTmCd	Opposite Broker Id	String	1	
21	ctclId	CTCL code	double	8	400028023057130
22	status	Trade Status. Refer Section "Transcodes"	String	1	P
23	TmCd	Member Code	String	5	09018
24	sym	Symbol	String	10	USDINR
25	ser	Series	String	2	
26	inst	Instrument	String	6	FUTCUR
27	expDt	Expiry Date (in milliseconds from 1980)	int	4	1259280000
28	strPrc	Strike Price in paise	int	4	-1
29	optType	Option Type for Option Contract. Refer Section "Transcodes"	String	2	
30	fill1	Filler	String	10	
31	fill2	Filler	String	10	
32	fill3	Filler	String	10	
33	fill4	Filler	String	10	
34	fill5	Filler	String	10	
35	fill6	Filler	String	10	
36	fill7	Filler	String	10	
37	fill8	Filler	String	10	

Note: Client modifications (Transaction Code: 5445) will be shown as part of the trade inquiry response.

6.2 Action Inquiry (Approval/Rejection/Approve ALL Response)

UAT: <https://www.devconnect2nse.com/notis-cd/actions-inquiry>

Production/LIVE: <https://www.connect2nse.com/notis-cd/actions-inquiry>

➔ Sample request call (ALL Actions)

```
POST /notis-cd/actions-inquiry HTTP/1.1
Host: www.devconnect2nse.com
Authorization: Bearer 3f64e567-04f9-43b8-9d24-e99856b24151
nonce: MjAwMTlwMTcxNjEyMjE1OTE6ODk0MjY3

{
  "version": "1.0",
  "data": {
    "msgId": "00240201310140000001",
    "dataFormat": "CSV:CSV",
    "actionsInquiry": "0,ALL, "
  }
}
```

➔ Sample request call (TMACTIONS Actions)

NOTE: This filter is only applicable to Clearing Members that want to view only the actions as a Trading Member.

```
POST /api/notis-cd/actions-inquiry HTTP/1.1
Host: www.connect2nse.com
Authorization: Bearer 3f64e567-04f9-43b8-9d24-e99856b24151
nonce: MjAwMTlwMTcxNjEyMjE1OTE6ODk0MjY3

{
  "version": "1.0",
  "data": {
    "msgId": "00240201310140000001",
    "dataFormat": "CSV:CSV",
    "actionsInquiry": "0,TMACTIONS, "
  }
}
```

➔ Request Structure

Request Data Payload (JSON)				
Sr. No.	Parameter Name	Data Type	Description	Sample Value
1	version	String	API version	1.0
2	data.msgId	String	Unique request number for the each request <CODE><YYYYMMDD><nnnnnnnn> • MEMBERCODE – Member code (Length : 5) • YYYYMMDD – Date format • nnnnnnn – Sequence no. starting from one i.e. For first request of the day, it should be (0000001).	00240201310140000001
3	data.dataformat	String	Request data format : Response data format	CSV:CSV
4	data.actionsInquiry	CSV	Data Structure specified below	Refer “Sample Request”

Actions Download Request Packet Structure				
Field Name	Description	Data Type	Size (in bytes)	Remarks
seqNo	Action Sequence number till where server had already sent data information In the previous request. For first download request of the day, it should be 0.	long	8	0
srchFilter	Search Filter All (Default)	String	50	<ul style="list-style-type: none"> ALL – All Actions TMACTIONS – Clearing Member to view actions as a Trading Member (Only applicable to Clearing Members)
fill1	Filler	String	10	
fill2	Filler	String	10	

➔ Sample Response

```
{
  "status": "success",
  "messages": {
    "code": "01010000"
  },
  "data": {
    "msgId": "00240201310140000001",
    "actionsInquiry": "1,20191031,,,32,3^0,30,49403,1258202712,14,DBNK00003803^0,31,18335,1258296409,5,DBNK00003803^0,32,22512,1258296409,4,DBNK00003803"
  }
}
```

➔ Response Structure

Response Data Payload (JSON)				
Sr. No.	Parameter Name	Data Type	Description	Sample Value
1	status	String	Response status	success/error
2	messages.code	String	Refer Section "Message based response code".	01010000
3	data.msgId	String	Unique request number sent in request.	00240201310140000001
4	data.actionsInquiry	CSV	Data Structure specified below	Refer Sample Response

Actions Download Response Packet Structure				
Field Name	Description	Data Type	Size (in bytes)	Remarks
Control Record				
sysinfoResData	System Info Response Structure	System Info Response Structure	Size of (System Info Response Structure)	Structure details give below
actResData	Actions Response Data Structure	Response Data Structure	Size of Response Data Structure	Structure details give below

➔ System Info Response Structure

System Info Response Structure				
Field Name	Description	Data Type	Size (in bytes)	Sample
mktSts	Market Status Refer Section “Transcodes”.	Short	2	1
currTrdDate	Current Trade Date (YYYYMMDD)	long	8	20191031
sfill1	Filler	String	10	
sfill2	Filler	String	10	

➔ Action Response Data Structure

Actions Response Data Structure				
Field Name	Description	Data Type	Size (in bytes)	Sample
maxSeqNo	Max sequence number sent in response	long	8	32
noOfRec	Count of actions sent in response	int	4	3
Data Records				
actionsOutput	Array Of AppRejAction Structure	Array Of Actions Structure	Size of (Array Of Actions Structure)	Structure details give below

AppRejAction Data Structure				
Field Name	Description	Data Type	Size (in bytes)	Sample
errCd	Action Response error code	short	2	Refer Section “Async Response codes”.
seqNo	Trade Sequence number	int	4	Sequence number of the trade for which action is received 30
actTrdNo	Trade Number	long	8	49403
actDtTm	Action Date Time	int	4	Date time in milliseconds from 1980

				1258202712
actId	Action Id	short	2	Refer Section "Transcodes". 14
cpCd	Custodial Participant Code	String	10	DBNK00003803

- **Workflow**
 - Trade/Action download works on sequence number basis present in individual trade/action response packet (*seqNo*).
 - The sequence number signifies the sequence of events for a single trade/action lifecycle. Thus every event occurred with respect to a particular trade/action will have a new sequence No.
 - On trades/actions download request, maximum trades/actions sequence no available should be sent. If there are no trades/actions present, it has to send the sequence as 0. API shall interpret the request, and will fetch "n" (Configurable) number of trades/actions, whose trades/actions sequence number is greater than that sent by client. The fetched trades will be sent back to client in response.
 - The trades/actions received by client in response packet are to be stored at client end. On subsequent trades/actions download request, client has to again send the maximum trades/actions sequence no available with him.

7 Transcodes

7.1 Market Type

1	Normal
2	Odd Lot
3	Spot

7.2 Market Status

1	Preopen shutdown
2	Normal Market Preopen ended
3	Open Msg
4	Close Msg
5	Closing Start
6	Closing End

7.3 Transaction Code

6001	Original Trade
5525	Trade Modification Approval
5565	Control Trade Modification
5520	Trade Cancellation Approval
5560	Control Trade Cancellation
5530	Trade Cancellation Rejection
5445	Trade modification (Client Modification)
5440	Trade Cancellation

7.4 Activity Type

2	Original Trade
7	Trade Cancellation
104	Quantity modification
105	Buy Account No. modification
106	Sell Account No. modification
107	Buy & Sell Account No.modification
109	Buy Trade Cancellation due to modification
110	Sell Participant Cancellation due to modification
111	Buy & Sell Trade Cancellation due to modification

7.5 Book Type

1	Regular Lot
2	Special Terms
3	Stop Loss / MIT
4	Negotiated Trade
5	Odd Lot
6	Spot

7.6 Client Type

1	Cli
2	Pro

7.7 Buy Sell Flag

1	BUY
2	SELL

7.8 Trade Status

P	Pending
R	Reject
A	Approve

7.9 Is Approval Flag

1	Approve
0	Reject

7.10 Action Id

2	Buy SI Generated
3	Sell SI Generated
4	AppRej Buy Approval
5	AppRej Sell Approval
6	Buy Side CP Modification (Old CP)
7	Sell Side CP Modification (Old CP)
8	Buy Side CP Modification (New CP)
9	Sell Side CP Modification (New CP)
14	AppRej Buy Rejected
15	AppRej Sell Rejected
16	Buy SI Cancelled
17	Sell SI Cancelled

8 Response Codes

There can be three types of response codes

- HTTP response codes
- Message based response codes
- Async response codes

8.1 HTTP response code

- HTTP responses shall be generated during login with success or failure status
- HTTP response shall also be generated in case of any authentication/input validation failure of the message
- HTTP response codes are as follows:

HTTP Response Codes			
Sr. No.	Reason	Meaning	HTTP Response Codes
1	SUCCESS	Request was handled successfully	200
2	UNKNOWN_ERROR	Internal Server Error: Internal server error has occurred in our platform.	500
3	SVC_UNAVAILABLE	The server is currently unable to handle the request due to a temporary overloading or maintenance of the server.	503
4	METHOD_NOT_ALLOWED	Unsupported HTTP Method: A request was made for a resource using a request method not supported by that resource (e.g. using POST instead of GET).	405
5	BAD REQUEST	PARAMETER_ABSENT - There's a required parameter which is not present in the request.	400
6	BAD REQUEST	DATA_INVALID - The data is not in correct format and not recognized by our system.	400
7	BAD REQUEST	DATA_FORMAT_REJECTED - Unsupported Data format parameter value	400
8	UNAUTHORIZED: Failed to authenticate the request	CONSUMER_KEY_UNKNOWN - The provided Consumer Key (API key) is not registered in our system or service is not registered.	401
9	UNAUTHORIZED: Failed to authenticate the request	TOKEN_INVALID - The provided token is not registered in our system	401
10	UNAUTHORIZED: Failed to authenticate the request	UNAUTHORIZED: * Unauthorized requestor IP address. * API access disabled	401
11	TOKEN_EXPIRED	The TEMPORARY access token generated by the platform has expired and can no longer be used.	572
12	PERMISSION_DENIED	Subscriber has temporarily disallowed access to his private data.	403
13	REQUEST_NOT_FOUND	Registration request not found	570

8.2 Message based response code

- Message based response code shall be populated in the field “**code**” of the JSON response message
- It shall be of below format
 - First four characters (Field Identifier): refers to specific field or the entire message
 - Next characters (Validation code): refers to specific validation failure or success.
Success code shall be populated only on successful acceptance of the message.

8.2.1 Field Identifier is as follows:

Sr. No.	Module	Field Name	Field Identifier
1	Entire Message	NA	0101
2	Input Data Parameter	msgId	0102
3	Input Data Parameter	msgPrepDt	0105
4	Input Data Parameter	msgPrepTm	0106
5	Input Data Parameter	isApproval	0109
6	Input Data Parameter	seqNo	0107
7	Input Data Parameter	srchFilter	0108
8	Input Data Parameter	noOfRec	0110

8.2.2 Validation codes are as follows:

Sr. No.	Validation	Validation Type	Validation Code	Validation performed on Field
1	Submitted to server successfully	Message Level	0000	Entire Message
2	All HTTP status codes	HTTP error codes	HTTP Response codes. Refer section "HTTP Response Code".	Entire Message
3	Mismatch in control and data record	Message Level	0200	Entire Message
4	Minimum Required Length	Generic	0201	msgId
5	Maximum Required Length	Generic	0202	msgId
6	Mandatory field	Generic	0204	msgId, isApproval, noOfRec, seqNo, srchFilter, trdDate
7	Data Format like Msg Id / Date Format	Generic	0206	msgId, trdDate
8	Minimum allowed value	Generic	0207	seqNo, noOfRec
9	Maximum allowed value	Generic	0208	noOfRec
10	Invalid Value	Generic	0209	seqNo, isApproval, srchFilter, trdDate
11	System Error	Generic	0241	NA
12	Service Unavailable	Generic	0242	NA
13	Request Parsing Error : Invalid Request Structure	Generic	0243	NA

8.2.3 Sample for success or failure code

- Example for Generic Error Code

Let's assume that msgId field holds value ABCD201340402132165, which turns out to be an error "Invalid Data Format". Error Code that will be generated is as shown below:

Field Identifier: 0102

Validation Code: 0206

code = combination of "Field Identifier" and "Validation Code" = 01020206

- Example for Field Error Code

Let's assume that seqNo field holds value -1, which turns out to be an error "Minimum allowed value". Error Code that will be generated is as shown below:

Field Identifier: 0107

Validation Code: 0207

code = combination of "Field Identifier" and "Validation Code" = 01070207

- Example for Success code (Submitted to server successfully)

Let's assume that message for approval/rejection is successful, success code that will be generated is as shown below:

Field Identifier: 0101 (which is the identifier of the entire message)

Validation Code: 0000

code = combination of "Field Identifier" and "Validation Code" = 01010000

- Example for HTTP error code

Let's assume that the invalid request scenario due to BAD Request, error code that will be generated is as shown below:

Field Identifier: 0101 (which is the identifier of the entire message)

Validation Code: 400

code = combination of "Field Identifier" and "Validation Code" = 0101400

8.3 Async response code

Async response code shall be populated in the field "errCd" of the message

Error	Error Code
Success	0
System in wrong state	1
Invalid Contract	2
Invalid Participant	3
Trade not found	4
Trade already cancelled	5

System Error	6
Trade already approved	7
Trade already rejected	8
Outstanding alert	9
Invalid user	10
Invalid data	11
Clearing Member is in VC mode. Trade Approval/Rejection not allowed.	12
Clearing Member is Disabled. Trade Approval/Rejection not allowed.	13
Not Latest Trade	-12
Approve All request rejected-Invalid market status	-19
Invalid Seq No	-20
Invalid Clearing Member	-21
Invalid CP code	-22
Invalid buy/sell flag	-23
Invalid instrument	-24
Invalid symbol	-25
Invalid strike price	-26
Invalid expiry date	-27
Invalid option type	-28
Invalid trade quantity	-29
Invalid trade price	-30
Invalid order number	-31
Invalid trade number	-32
Invalid broker id	-33
Already submitted	-50
Already approved	-51
Already rejected	-52

9 Contingencys

In case of any failure such as network, application, high bandwidth utilization at NSE or the MEMBER end, login workflow has to be re-initiated.

10 Usage Guidelines

- Members should limit requests to **15 seconds** between each request to the Trade Inquiry API/token service.

- Members can send requests to the API between 6:30 AM to 5 AM next day. Kindly note that Notis services shall not be available between 5 AM to 6:30 AM due to maintenance activity.
- Failure to adhere to the above guidelines will result in removal of IP from whitelist which means that member will not be able to access the API until IP is re-added to the whitelist.